

*DESCRIPTION: Single Phase, On/Off Control*  
*APPLICATION: Constant Resistance Loads*

Model Number	Fuse Amps	kVA @ Max Rated Volts	Open Chassis Dimensions Inches			Open Chassis List Price	Ventilated Dimensions H x W x D	Enclosure List Price Adder
			Height	Width	Depth			
<b>SINGLE POLE, SINGLE PHASE, 120 VAC INPUT, 118 VAC OUTPUT, 10-400Hz</b>								
11D-1-10i	10	1.2	6.25	3.5	3	53.00	10 6 6	Contact Factory
11D-1-20i	20	2.4	6.25	3.5	3	97.00	10 6 6	***
11D-1-30i	30	3.6	6.25	3.5	4	112.00	10 6 6	***
11D-1-50	50	6.0	12	5.5	6	182.00	14 12 8	***
11D-1-80	80	9.6	12	5.5	6	216.00	14 12 8	***
11D-1-120	120	14.4	12.5	6.5	8	434.00	20 16 9	***
11D-1-150	150	18.0	15	9.5	8	456.00	20 16 9	***
11D-1-250	250	30.0	25	9.5	8	675.00	30 20 9	***
11D-1-350	350	42.0	21	13	10.5	728.00	36 24 12	***
<b>SINGLE POLE, SINGLE PHASE, 240 VAC INPUT, 238 VAC OUTPUT (ALSO FOR 208/220/230 VAC INPUT)</b>								
11D-2-10i	10	2.4	6.25	3.5	3	56.00	10 6 6	Contact Factory
11D-2-15i	15	3.6	6.25	3.5	3	59.00	10 6 6	***
11D-2-20i	20	4.8	6.25	3.5	3	97.00	10 6 6	***
11D-2-30i	30	7.2	6.25	3.5	4	112.00	10 6 6	***
11D-2-50	50	12.0	12	5.5	6	182.00	14 12 8	***
11D-2-80	80	19.2	12	5.5	6	216.00	14 12 8	***
11D-2-120	120	28.8	12.5	6.5	8	434.00	20 16 9	***
11D-2-150	150	36.0	15	9.5	8	456.00	20 16 9	***
11D-2-250	250	60.0	25	9.5	8	675.00	30 20 9	***
11D-2-350	350	84.0	21	13	10.5	728.00	36 24 12	***
<b>SINGLE POLE, SINGLE PHASE, 480 VAC INPUT, 478 VAC OUTPUT (ALSO FOR 380/415/440 VAC INPUT)</b>								
11D-4-10	10	4.8	7	5.5	4.5	106.00	12 10 8	Contact Factory
11D-4-20	20	9.6	7	5.5	4.5	127.00	12 10 8	***
11D-4-30	30	14.4	7	5.5	5.5	139.00	12 10 8	***
11D-4-50	50	24.0	12	5.5	6	187.00	14 12 8	***
11D-4-80	80	38.4	12	5.5	6	216.00	14 12 8	***
11D-4-120	120	57.6	12.5	6.5	8	434.00	20 16 9	***
11D-4-150	150	72.0	15	9.5	8	456.00	20 16 9	***
11D-4-250	250	120	25	9.5	8	675.00	30 20 9	***
11D-4-350	350	168	21	13	10.5	728.00	36 24 12	***
11D-4-450	450	215	27	17	10.5	826.00	36 24 12	***
11D-4-600	600	288	27	17	10.5	1,495.00	42 30 12	***
11D-4-1200	1200	576	30	24	11	2,599.00	42 30 12	***

**NOTES:**

- Standard units actuated by external maintained contact closure (line voltage rated). For actuation by external voltage signal, see Option 27
- Standard units supplied with Factory installed 2-millisecond fuses.
- Effective 8/90, 10-30 Amp sizes at 120 and 240 VAC are replaced by 11Di version (suffix "i" in Model number)
- For recommended spare fuses, see FUSE CHART, page 36. Use of any other fuse voids all warranties.
- For multiple-pole mounting on common baseplate, multiply the list price for the required size by the number of poles and add Option 27 to each pole.
- Enclosures supplied by others must be properly ventilated. See VENT SCHEDULE, Page 37.
- Dimensions are approximate, refer to unit drawing for construction.  
*List prices may be subject to trade classification discounts contact your local Payne Controls Authorized Distributor or representative. Prices shown are subject to change without notice.*