

DESCRIPTION: Single Phase, Phase Angle Control

APPLICATION: Transformer Coupled and other Inductive Loads

Model Number	Max Amps	kVA @ Max Rated Volts	Open Chassis Dimensions Inches			Open Chassis List Price	Ventilated Dimensions H x W x D	Enclosure List Price Adder
			Height	Width	Depth			
SINGLE PHASE, 120 VAC INPUT, 0-118 VAC OUTPUT, 50/60Hz								
18D-1-10SW2i	10	1.2	7	5.5	3	312.00	12 10 8	Contact Factory
18D-1-30SW2	30	3.6	7	5.5	5.5	396.00	12 10 8	***
18D-1-80SW2	80	9.4	12	5.5	7	639.00	14 12 8	***
18D-1-150SW2	150	17.7	15	9.5	8	829.00	20 16 9	***
18D-1-350SW2	350	41.3	21	13	10.5	1,358.00	36 24 12	***
18D-1-600SW2	600	70.8	33	17	11	2,499.00	42 30 12	***
SINGLE PHASE, 240 VAC INPUT, 0-238 VAC OUTPUT, 50/60Hz (ALSO FOR 208/220/230 VAC INPUT)								
18D-2-10SW2i	10	2.4	7	5.5	3	312.00	12 10 8	Contact Factory
18D-2-30SW2	30	7.2	7	5.5	5.5	396.00	12 10 8	***
18D-2-80SW2	80	19.0	12	5.5	7	639.00	14 12 8	***
18D-2-150SW2	150	35.7	15	9.5	8	829.00	20 16 9	***
18D-2-350SW2	350	83.3	21	13	10.5	1,358.00	36 24 12	***
18D-2-600SW2	600	142.8	33	17	11	2,499.00	42 30 12	***
SINGLE PHASE, 480 VAC INPUT, 0-478 VAC OUTPUT, 50/60Hz (ALSO FOR 380/415/440 VAC INPUT)								
18D-4-10SW2	10	4.8	10	5.5	4.5	329.00	12 10 8	Contact Factory
18D-4-30SW2	30	14.4	10	5.5	5.5	404.00	12 10 8	***
18D-4-80SW2	80	38.2	12	5.5	7	639.00	14 12 8	***
18D-4-150SW2	150	71.7	15	9.5	8	829.00	20 16 9	***
18D-4-350SW2	350	167	21	13	10.5	1,358.00	36 24 12	***
18D-4-600SW2	600	287	33	17	11	2,499.00	42 30 12	***

NOTES:

- Standard units supplied with:
 - Manual control potentiometer on 2 feet of cable
 - Control isolation transformer (except where noted †)
 - Factory installed 2-millisecond fuses
 - 1/2 second soft start
 - Oversized SCR's
- For recommended spare fuses, see FUSE CHART, Page 36. Use of any other fuse voids all warranties.
- Enclosures supplied by others must be properly ventilated. See VENT SCHEDULE, Page 37.
- Dimensions are approximate, refer to unit drawing for construction.

List prices may be subject to trade classification discounts. Contact your local Payne Controls Authorized Distributor or representative.

Prices shown are subject to change without notice.

OPTION NAME	OPTION ORDER No.	OPTION DESCRIPTION	LIST PRICE ADDER
VOLTAGE LIMIT	9	RMS Output Voltage Limit (Field adjustable)	25.00
MILLIAMP CONTROL	11A 11B 11C 11D 11E 11F 11G 11H	For closed-loop applications only. (See Option 20 for open-loop applications) 1-5 ma., ≤1000 Ω 2-10ma., ≤1000 Ω 4-20 ma., ≤600 Ω 12-20 ma., ≤600 Ω 10-50 ma., ≤300 Ω 1-5 volts DC 2-10 volts DC Other. Specify ma. range and input impedance.	38.00
CURRENT LIMIT	12	RMS Output Current Limit (Field Adjustable, includes current transformer)	115.00
ISOLATED CHASSIS	14A 14B	For installation in non-vented enclosures. Electrically Isolated Chassis, 10-30A Electrically Isolated Chassis, 50-80A	65.00 97.00
OPTICALLY ISOLATED ma. EXTERNAL CONTROL CARD	20A 20B 20C 20D 20E 20H	Optically isolated. May be field installed. Suitable for open-loop control. 1-5 ma., ≤1000 Ω 2-10ma., ≤1000 Ω 4-20 ma., ≤600 Ω 12-20 ma., ≤600 Ω 10-50 ma., ≤300 Ω Other. Specify ma. range and input impedance.	65.00
HEATSINK OVERTEMP SWITCH	24A 24B	Overtemp trip of controller. For external indicating circuit or alarm.	55.00
120V PILOT	28	120 VAC On/Off Pilot Control	38.00
EXTERNAL POWER	33	External trigger circuit power. Specify voltage to be supplied.	38.00
277 VAC INPUT	18D- 3 -etc.	Rated for 277 VAC Input. (Change Model No. from 18D-4-etc. to 18D-3-etc.)	N/C
550 VAC INPUT	18D- 5 -etc.	Rated for 550 VAC Input. (Change Model No. from 18D-4-etc. to 18D-5-etc.)	38.00
600 VAC INPUT	18D- 6 -etc.	Rated for 600 VAC Input. (May require size increase of base model.) (Change Model No. from 18D-4-etc. to 18D-6-etc.)	210.00

18D-SW OPTION NOTES:

- To order, specify option number separately, and add option price to control list price.
- See page 38 for detailed option description.
- Options must be ordered with control (except Option 20)
- Certain combinations of options may not be compatible. Consult local representative or factory.
- Consult factory for option requirements not shown.