

DESCRIPTION: Single Phase A.C. Input, Variable D.C. Output Control
APPLICATION: Inductive or Resistive D.C. Loads

Model Number	Fuse Amps	Open Chassis Dimensions Inches			List Price
		Height	Width	Depth	
SINGLE PHASE, 120 VAC INPUT, 0-107 VDC OUTPUT, 50/60Hz					
36TBP-1-5	5	3.25	2.65	3.4	108.00
36TBP-1-10	10	3.33	4.5	3.1	118.00
SINGLE PHASE, 240 VAC INPUT, 0-215 VAC OUTPUT, 50/60Hz (ALSO FOR 208/220/230 VAC INPUT)					
36TBP-2-5	5	3.25	2.65	3.4	118.00
36TBP-2-10	10	3.33	4.5	3.1	140.00

NOTES:

1. Model 36TBP controls designed for through-the-door mounting. (See Fig. 1)
 2. All 36TBP controls have factory tested and approved 2-millisecond fuses installed.
 3. For higher voltage or amperage ratings, or for control features not shown here, refer to Model 36D, page 30.
 4. For recommended spare fuses, see FUSE CHART, page 36. Use of any other fuse voids all warranties.
 5. Enclosures supplied by others must be properly ventilated. See VENT SCHEDULE, page 37.
- List prices may be subject to trade classification discounts. Contact your local Payne Controls Authorized Distributor or representative.

Prices shown are subject to change without notice.



Fig. 1 Model 36TBP 5 AMP



Fig. 1 Model 36TBP 10 AMP